
Newfoundland Labrador Hydro (NLH) Supply and Demand Status Report Filed Monday, December 08, 2014



Supply Notes for December 07, 2014^{1,2}

- A As of 1000 hours, November 21, 2014, Nalcor Exploits Unit 4 unavailable due to a forced outage (30 MW). Net impact to system 4 MW (the excess water utilised by other Nalcor Grand Falls Units 5 to 8).
- At 1050 hours, December 07, 2014, Hardwoods Gas Turbine End B returned to service (25 MW).
- At 1613 hours, December 07, 2014, Holyrood Unit 2 returned to service (170 MW).
- At 2100 hours, December 07, 2014, Hardwoods Gas Turbine End A returned to service (25 MW).

Section 2 Island Interconnected Supply and Demand									
Mon, Dec 08, 2014 Island System Outlook ³		Seven-Day Forecast	•	Temperature (°C)		Island System Daily Peak Demand (MW)			
				Morning	Evening	Forecast	Adjusted ⁶		
Available Island System Supply:5	1,880	MW	Monday, December 08, 2014	-9	-9	1,500	1,420		
NLH: ⁴	1,660	MW	Tuesday, December 09, 2014	-7	-4	1,410	1,335		
Other Island Generation:	220	MW	Wednesday, December 10, 2014	1	3	1,290	1,215		
			Thursday, December 11, 2014	4	5	1,250	1,175		
Current St. John's Temperature:	-11	°C	Friday, December 12, 2014	9	7	1,160	1,085		
Current St. John's Windchill:	-21	$^{\circ}$ C	Saturday, December 13, 2014	6	3	1,275	1,200		
7-Day Island Peak Demand Foreca	ast: 1,500	MW	Sunday, December 14, 2014	8	9	1,125	1,050		

Supply Notes for December 08, 2014³

- Otes: 1. Generation outages for running and corrective maintenance are included. These are not unusual for power system operations. They generally do not impact customer supply. The power system operators schedule outages to system equipment whenever possible to coincide with periods when customer demands are low and sufficient supply reserves are available. However, from time to time equipment outages are necessary and reserves may be impacted.
 - 2. Due to the Island Interconnected System being isolated from the larger North American grid, when there is a sudden loss of large generating units some customer's load must be interrupted for short periods to bring generation output equal to customer demand. This automatic action of power system protection, referred to as underfrequency load shedding, is necessary to ensure the integrity and reliability of system equipment. Underfrequency events typically occur 5 to 8 times per year on the Island Interconnected System and the resultant customer load interruptions are generally less than 30 minutes.
 - 3. As of 0800 Hours
 - 4. Gross output including station service at Holyrood (24.5 MW) and improved NLH hydraulic output due to water levels (35 MW). Includes NLH Power Purchases.
 - 5. Gross output from all Island sources (including Note 4).
 - 6. Adjusted for CBP&P interruptible load (when applicable) and the impact of voltage reduction.

Section 3 Island Peak Demand Information Previous Day Actual Peak and Current Day Forecast Peak						
Sun, Dec 07, 2014	Actual Island Peak Demand ⁷	16:50	1,275 MW			
Mon, Dec 08, 2014	Forecast Island Peak Demand		1,500 MW			

Notes: 7. Island Demand is supplied by NLH generation and purchases, plus generation owned and operated by Newfoundland Power and Corner Brook Pulp & Paper (Deer Lake Power, DLP).