

## Newfoundland Labrador Hydro (NLH) Supply and Demand Status Report Filed Monday, February 12, 2018

A As of 2115 hours, January 04, 2018, Stephenville Gas Turbine available at 25 MW (50 MW).

- **B** As of 1204 hours, February 03, 2018, Holyrood Unit 1 unavailable 70 MW (170 MW).
- C As of 0809 hours, February 07, 2018, Holyrood Unit 3 available at 105 MW (150 MW).
- D As of 1550 hours, February 08, 2018, Holyrood Unit 2 available at 127 MW (170 MW).

Section 2 Island Interconnected Supply and Demand									
Sat, Feb 10, 2018	Island System Outlook <sup>3</sup>			Seven-Day Forecast	Temperature (°C)		Island System Daily Peak Demand (MW)		
					Morning	Evening	Forecast	Adjusted <sup>7</sup>	
Available Island System Supply:5		1,735	MW	Saturday, February 10, 2018	-8	-2	1,470	1,317	
NLH Generation: <sup>4</sup>		1,410	MW	Sunday, February 11, 2018	6	-2	1,415	1,307	
NLH Power Purchases: <sup>6</sup>		110	MW	Monday, February 12, 2018	0	4	1,400	1,223	
Maritime Link Imports:		-	MW	Tuesday, February 13, 2018	-6	-11	1,655	1,545	
Other Island Generation:		215	MW	Wednesday, February 14, 2018	-11	-4	1,645	1,401	
Current St. John's Temperature & Windchill:	-10 °C	-16	°C	Thursday, February 15, 2018	1	1	1,330	1,184	
7-Day Island Peak Demand Forecast:		1,655	MW	Friday, February 16, 2018	3	-7	1,530	1,421	

Notes: 1. Generation outages for running and corrective maintenance are included. These are not unusual for power system operations. They generally do not impact customer supply. The power

- system operators schedule outages to system equipment whenever possible to coincide with periods when customer demands are low and sufficient supply reserves are available. However, from time to time equipment outages are necessary and reserves may be impacted.
- 2. Due to the Island System having no synchronous connections to the larger North American grid, when there is a sudden loss of large generating units some customer's load must be interrupted for short periods to bring generation output equal to customer demand. This automatic action of power system protection, referred to as under frequency load shedding, is necessary to ensure the integrity and reliability of system equipment. Under frequency events typically occur 5 to 8 times per year on the Island Interconnected System and the resultant customer load interruptions are generally less than 30 minutes.
- 3. As of 0800 Hours.
- 4. Gross output including station service at Holyrood (24.5 MW) and improved NLH hydraulic output due to water levels (35 MW).
- 5. Gross output from all Island sources (including Note 4).
- 6. NLH Power Purchases include: CBPP Co-Gen, Nalcor Exploits, Rattle Brook, Star Lake, Wind Generation, Vale capacity assistance (when applicable).
- 7. Adjusted for CBP&P, Vale and Praxair interruptible load, Maritime Link Exports and the impact of voltage reduction (when applicable).

	Section 3						
Island Peak Demand Information Previous Day Actual Peak and Current Day Forecast Peak							
Sat, Feb 10, 2018	Forecast Island Peak Demand		1,470 MW				